



### For Air Cooled Models

Item	Description	Model 4200	Model 4204	Model 4204PR	Model 4210
1	Circulating Pump Only	C19487	C19487	C31464	C31464
2	Circulating Pump Complete	C15969	C15969	N/A	N/A
3	Circulating Pump Motor	C15843-2	C15843-2	N/A	N/A
3a	Motor Kit, G.E.	N/A	N/A	57371	57371
3b	Motor Kit, Emerson	N/A	N/A	57371EM	57371EM
4	Circulating Pump Coupling	N/A	N/A	C27225	C27225
5	Pump Shaft & Impeller Kit	C22436-2	C22436-2	N/A	N/A
6	Condenser Fan Blade	N/A	C3150-3	C3150-3	N/A
7	Condenser Fan Motor	N/A	C6121	C6121	N/A
8	Condensing Unit (134A)	C22613	C22604	C22604	C22600
9	Compressor Only (134A)	57507	57672	57672	C22600-1
10	Temperature Control	C12213A	C12213A	C12213A	C12213A
11	Top (front) Cover	C18819	C18821	C18821	N/A
12	Top (back) Cover	C18815-1	C18817-1	C19940-1	C29483
13	Front Grille	C15074	C15075	C15075	C24907
	Wire Harness (not shown)	C19676A1	C19677A1	C19677A1	C27406A1
	Dow Therm (1 gallon)	C15426	C15426	C23820	

MODEL NOS.	Air-Cooled	4200	4204	4204PR	4210
	Water-Cooled	N/A	4204W	4204WPR	4210W
DIMENSIONS EXTERIOR (mm.)	Length A Dim.	15 <sup>3</sup> / <sub>4</sub> " (400)	21 <sup>1</sup> / <sub>4</sub> " (540)	21 <sup>1</sup> / <sub>4</sub> " (540)	27 <sup>3</sup> / <sub>4</sub> " (705)
	Depth B Dim.	14 <sup>3</sup> / <sub>4</sub> " (375)	15 <sup>1</sup> / <sub>4</sub> " (387)	15 <sup>1</sup> / <sub>4</sub> " (387)	17 <sup>3</sup> / <sub>4</sub> " (451)
	Height C Dim.	24 <sup>1</sup> / <sub>2</sub> " (622)	29" (737)	33 <sup>3</sup> / <sub>4</sub> " (857)	21 <sup>1</sup> / <sub>4</sub> " (540)
CONDENSING UNIT H.P.		1/5	1/3	1/3	1/2
AMPS		7.0	10.6/10.4	14.1/14.0	14.6/14.7
PUMP		Centrifugal	Centrifugal	Procon	Procon
SHIPPING WEIGHT lbs. (kg.)		93 (42.2)	135 (61.2)	145 (65.8)	210 (95.3)
MAXIMUM FOOTAGE IN SYSTEM		50	100	150	300
DOW THERM* REQUIRED (ltr.)		1 gal. (3.8)	2 gals. (7.6)	2 gals. (7.6)	4 gals. (15)
B.T.U.'s		1700	2550	2550	3800 RE-
FRIGERANT CHARGE (grams)		6.5 oz. (184)	10 oz. (283)	10 oz. (283)	15/24 oz.(425/680)
REFRIGERATION	134a capillary tube-type hermetic condensing unit with service valves.				
ELECTRICAL	120 Volt, 60 hz., 1 Phase AC. If a plug-in cord will be used, order Perlick's Part No. C22296 Cord Kit, 16 gauge, 3 wire with wire nuts.				
PLUMBING	<b>For Water-Cooled Units Only:</b> Water Inlet and Outlet <sup>3</sup> / <sub>8</sub> " male flare.				
OPTIONAL ACCESSORIES	4208A	Set of wall-mounting brackets for 4200 and 4204 power paks	4209	Set of wall-mounting brackets for 4210 power paks	
	C21499A	Stand with table top & storage shelf	7860-18A	Set of four adjustable legs for 4210 power pak	
	C23625	Set of four adjustable legs for table stand			

\*Dow Therm is a registered trademark of the Dow Chemical Company.

**For 4200 and 4204 Series**

